
PHF FX10-30X55



Bushing no.	FX10
d (mm)	30
d (in)	1.18
D (mm)	55
d _w (mm)	-
L (mm)	-
L ₁ (mm)	17
L ₂ (mm)	20
L ₃ (mm)	-
B (mm)	27.5
D ₁ (mm)	-
d_1 (mm)	-
e (mm)	-
F _t Transmissible axial force (kN)	33
M _t Transmissible	500
torque (Nm)	
P _w Shaft surface	175
pressure (N/mm²)	
P _n Hub surface	95
pressure (N/mm²)	10
Clamp screws Qty	M6
Clamp screws size	IVIO



[®] SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

Clamp screws nut	-
M _s Screw	15
tightening torque	
(Nm)	
Weight (kg)	0.3

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

