
Bushings and Hubs FX keyless bushings

## PHF FX20-65X84



Bushing no.	FX20
d (mm)	65
d (in)	2.56
D (mm)	84
d <sub>w</sub> (mm)	-
L (mm)	-
L <sub>1</sub> (mm)	55
L <sub>2</sub> (mm)	72
L₃ (mm)	80
B (mm)	88
D <sub>1</sub> (mm)	111
d <sub>1</sub> (mm)	-
e (mm)	-
F <sub>t</sub> Transmissible	94
axial force (kN)	
M <sub>t</sub> Transmissible	3070
torque (Nm)	70
P <sub>w</sub> Shaft surface pressure (N/mm <sup>2</sup> )	70
$P_n$ Hub surface	55
pressure (N/mm <sup>2</sup> )	
Clamp screws Qty	9
Clamp screws size	M8
Clamp screws nut	-
M <sub>s</sub> Screw	41
tightening torque	
(Nm)	
Weight (kg)	2.1

 ® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

