
Bushings and Hubs FX keyless bushings

## PHF FX20-110X140



Bushing no.	FX20
d (mm)	110
d (in)	4.33
D (mm)	140
d <sub>w</sub> (mm)	-
L (mm)	-
L <sub>1</sub> (mm)	90
L <sub>2</sub> (mm)	114
L <sub>3</sub> (mm)	128
B (mm)	140
D <sub>1</sub> (mm)	180
d <sub>1</sub> (mm)	-
e (mm)	-
F <sub>t</sub> Transmissible	290
axial force (kN)	
M <sub>t</sub> Transmissible	16000
torque (Nm)	80
P <sub>w</sub> Shaft surface pressure (N/mm <sup>2</sup> )	80
$P_n$ Hub surface	65
pressure (N/mm <sup>2</sup> )	
Clamp screws Qty	12
Clamp screws size	M12
Clamp screws nut	-
M <sub>s</sub> Screw	145
tightening torque	
(Nm)	0.7
Weight (kg)	8.7

® SKF is a registered trademark of the SKF Group
© SKF Group 2012

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

