
Bushings and Hubs FX keyless bushings

## PHF FX60-240X305



Bushing no.	FX60
d (mm)	240
d (in)	9.45
D (mm)	305
d <sub>w</sub> (mm)	-
L (mm)	-
L <sub>1</sub> (mm)	134
L <sub>2</sub> (mm)	146
L₃ (mm)	-
B (mm)	162
D <sub>1</sub> (mm)	-
d <sub>1</sub> (mm)	-
e (mm)	-
F <sub>t</sub> Transmissible	2017
axial force (kN)	
M <sub>t</sub> Transmissible	242000
torque (Nm)	
P <sub>w</sub> Shaft surface	166
pressure (N/mm²)	
P <sub>n</sub> Hub surface	131
pressure (N/mm²)	
Clamp screws Qty	22
Clamp screws size	M16
Clamp screws nut	-
M <sub>s</sub> Screw	355
tightening torque	
(Nm)	
Weight (kg)	27

 ® SKF is a registered trademark of the SKF Group
 © SKF Group 2012
 The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising the second secon out of the use of the information contained herein.

