
Bushings and Hubs FX keyless bushings

PHF FX80-35X45



Bushing no.	FX80
d (mm)	35
d (in)	1.38
D (mm)	45
d _w (mm)	-
L (mm)	-
L ₁ (mm)	8
L ₂ (mm)	-
L₃ (mm)	-
B (mm)	21.5
D ₁ (mm)	58
d ₁ (mm)	-
e (mm)	-
F _t Transmissible	13.1
axial force (kN)	
M _t Transmissible	230
torque (Nm)	
P _w Shaft surface	153
pressure (N/mm²)	100
P_n Hub surface	120
pressure (N/mm²)	
Clamp screws Qty	-
Clamp screws size	-
Clamp screws nut	KM8
M _s Screw	480
tightening torque	

 ® SKF is a registered trademark of the SKF Group
 © SKF Group 2012
 The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



(Nm)	
Weight (kg)	0.17

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising the second secon out of the use of the information contained herein.

