
Bushings and Hubs FX keyless bushings

## PHF FX190-44X80



Buching no	FX190
Bushing no.	44
d (mm)	••
d (in)	1.73
D (mm)	80
d <sub>w</sub> (mm)	32
L (mm)	25.5
L <sub>1</sub> (mm)	20
L <sub>2</sub> (mm)	-
L₃ (mm)	-
B (mm)	0
D <sub>1</sub> (mm)	-
d <sub>1</sub> (mm)	61
e (mm)	2.75
F <sub>t</sub> Transmissible	64
axial force (kN)	
M <sub>t</sub> Transmissible	620
torque (Nm)	
P <sub>w</sub> Shaft surface	-
pressure (N/mm²)	
P <sub>n</sub> Hub surface	-
pressure (N/mm <sup>2</sup> )	
Clamp screws Qty	7
Clamp screws size	M6
Clamp screws nut	-
M <sub>s</sub> Screw	12
tightening torque	
(Nm)	
Weight (kg)	0.6

 ® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

