
Bushings and Hubs FX keyless bushings

## PHF FX190-75X138



r	
Bushing no.	FX190
d (mm)	75
d (in)	2.95
D (mm)	138
d <sub>w</sub> (mm)	55
L (mm)	32.5
L <sub>1</sub> (mm)	25
L <sub>2</sub> (mm)	-
L₃ (mm)	-
B (mm)	0
D <sub>1</sub> (mm)	-
d <sub>1</sub> (mm)	100
e (mm)	3.75
F <sub>t</sub> Transmissible	119
axial force (kN)	
M <sub>t</sub> Transmissible	2500
torque (Nm)	
P <sub>w</sub> Shaft surface	-
pressure (N/mm²)	
P <sub>n</sub> Hub surface	-
pressure (N/mm²)	
Clamp screws Qty	7
Clamp screws size	M8
Clamp screws nut	-
M <sub>s</sub> Screw	30
tightening torque	
(Nm)	
Weight (kg)	1.7

® SKF is a registered trademark of the SKF Group
© SKF Group 2012

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

