
## PHF FX400-150X200



Bushing no.	FX400
d (mm)	150
d (in)	5.91
D (mm)	200
d <sub>w</sub> (mm)	-
L (mm)	-
L <sub>1</sub> (mm)	104
L <sub>2</sub> (mm)	116
L <sub>3</sub> (mm)	-
B (mm)	130
D <sub>1</sub> (mm)	-
$d_1$ (mm)	-
e (mm)	-
F <sub>t</sub> Transmissible	985
axial force (kN)	
M <sub>t</sub> Transmissible	73800
torque (Nm)	1.65
P <sub>w</sub> Shaft surface	165
pressure (N/mm²) P <sub>n</sub> Hub surface	125
pressure (N/mm²)	120
Clamp screws Qty	16
Clamp screws size	M14
Clamp screws nut	-
M <sub>s</sub> Screw	230
tightening torque	
(Nm)	
Weight (kg)	10.9

 $<sup>\</sup>ensuremath{\mathbb{R}}$  SKF is a registered trademark of the SKF Group  $\ensuremath{\mathbb{C}}$  SKF Group 2012



The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.