
Bushings and Hubs FX keyless bushings

## PHF FX10-260X325



Bushing no.	FX10
d (mm)	260
d (in)	10.24
D (mm)	325
d <sub>w</sub> (mm)	-
L (mm)	-
L <sub>1</sub> (mm)	50
L <sub>2</sub> (mm)	56
L₃ (mm)	-
B (mm)	74
D <sub>1</sub> (mm)	-
d <sub>1</sub> (mm)	-
e (mm)	-
F <sub>t</sub> Transmissible	800
axial force (kN)	
M <sub>t</sub> Transmissible	104000
torque (Nm)	
P <sub>w</sub> Shaft surface	165
pressure (N/mm²)	
P <sub>n</sub> Hub surface	130
pressure (N/mm²)	
Clamp screws Qty	34
Clamp screws size	M16

 ® SKF is a registered trademark of the SKF Group
 © SKF Group 2012
 The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



Clamp screws nut	-
M <sub>s</sub> Screw	300
tightening torque	
(Nm)	
Weight (kg)	13

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising the second secon out of the use of the information contained herein.

