
## PHF FX10-400X495



Bushing no.	FX10
d (mm)	400
d (in)	15.75
D (mm)	495
d <sub>w</sub> (mm)	-
L (mm)	-
	84
L <sub>1</sub> (mm)	90
L <sub>2</sub> (mm)	-
L <sub>3</sub> (mm)	116
B (mm)	110
D <sub>1</sub> (mm)	-
$d_1$ (mm)	-
e (mm)	-
F <sub>t</sub> Transmissible	1610
axial force (kN)	
M <sub>t</sub> Transmissible	322000
torque (Nm)	120
P <sub>w</sub> Shaft surface	130
pressure (N/mm²)	105
P <sub>n</sub> Hub surface	103
pressure (N/mm²)	36
Clamp screws Qty	M22
Clamp screws size	IVIZZ



<sup>®</sup> SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

Clamp screws nut	-
M <sub>s</sub> Screw	790
tightening torque	
(Nm)	
Weight (kg)	46

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

