
## PHE 15GCKIT



Size	15 GC
Power per 100	24.6
r/min (kW)	
Power per 100	32.98
r/min (HP)	
Rated torque (Nm)	2350
Rated torque (lbft)	1733.27
Speed Max. (r/min)	6500
Bore diameter Min.	20
(mm)	
Bore diameter Min.	0.79
(in)	
Bore diameter	65
Max. (mm)	
Bore diameter	2.56
Max. (in)	
A (mm)	152
A (in)	5.98
B (mm)	101
B (in)	3.98
C (mm)	49
C (in)	1.93
D (mm)	86
D (in)	3.39
F (mm)	105
F (in)	4.13
H (mm)	19
H (in)	0.75
J (mm)	48

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



J (in)	1.89
M (mm)	61
M (in)	2.4
Gap G Min. (mm)	3
Gap G Min. (in)	0.12
Lubricant mass (kg)	0.07
Lubricant mass (lbs)	0.15
Coupling mass without bore and min. DBSE (kg)	9
Coupling mass without bore and min. DBSE (lbs)	19.84

 SKF is a registered trademark of the SKF Group
 SKF Group 2012
 The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising the second s out of the use of the information contained herein.

