LAGD 125/HFP15

r	
Product description	SYSTEM 24 single
	point automatic lubricator
D. I	125 ml in SYSTEM 24
Package size	
Grease capability	125 ml (4.25 fl. Oz US)
Nominal emptying	Adjustable; 1-12
time	months
Ambient temp.	-20 to 60°C (-5 to
range	140°F)
Maximum operat.	5 bar (75 psi)
pressure	· • ·
Drive mechanism	Gas cell which produces
Drive mechanism	inert gas
Connection thread	G 1/4
Max. feed line	1500 mm (59,1 in)
length with oil	
Intrinsically safe	II 1 GD Eex ia II C T6
approval	T85° I M 1 EEx ia I
Protection class	IP 68
Rec. storage temp.	20°C (70°F)
Storage life of	2
lubricator (years)	
<u> </u>	200 g (7,1 oz)
Weight approx. (oil	200 8 (1,1 02)
incl.)	



 [®] SKF is a registered trademark of the SKF Group
 © SKF Group 2012
 The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.