
PHE SM25-180DBSE



Distance Between	180
Shaft Ends (DBSE) Nominal	
Distance Between	7.09
Shaft Ends (DBSE)	
Nominal (in)	
Distance Between	198
Shaft Ends (DBSE)	
Max	7.8
Distance Between	7.8
Shaft Ends (DBSE) Max (in)	
Coupling size	90
Spacer Bush Size	2517
Bore Min (mm)	16
Bore Min (in)	0.63
Bore Max (mm)	60
Bore Max (in)	2.36
Coupling Bush Size	2517
Bore Min (mm)	16
Bore Min (in)	0.63
Bore Max (mm)	60
Bore Max (in)	2.36
Α	235
A (in)	9.25
В	108
B (in)	4.25
С	178

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



D 123 D (in) 4.84 E 273 E (in) - F 45 F (in) 1.77 G 22 G (in) 0.87 H 16 H (in) 0.63 J 14 J (in) 0.55 K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	C (:=)	7.01
D (in) 4.84 E 273 E (in) - F 45 F (in) 1.77 G 22 G (in) 0.87 H 16 H (in) 0.63 J 14 J (in) 0.55 K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174		
E 273 E (in) - F 45 F (in) 1.77 G 22 G (in) 0.87 H 16 H (in) 0.63 J 14 J (in) 0.55 K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	D	
E (in) - F	D (in)	4.84
F 45 F (in) 1.77 G 22 G (in) 0.87 H 16 H (in) 0.63 J 14 J (in) 0.55 K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	Е	273
F (in) 1.77 G 22 G (in) 0.87 H 16 H (in) 0.63 J 14 J (in) 0.55 K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	E (in)	-
G 22 G (in) 0.87 H 16 H (in) 0.63 J 14 J (in) 0.55 K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	F	45
G (in) 0.87 H 16 H (in) 0.63 J 14 J (in) 0.55 K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	F (in)	1.77
H 16 H (in) 0.63 J 14 J (in) 0.55 K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	G	22
H (in) 0.63 J 14 J (in) 0.55 K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	G (in)	0.87
J 14 J (in) 0.55 K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	Н	16
J (in) 0.55 K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	H (in)	0.63
K 9 K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	J	14
K (in) 0.35 L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	J (in)	0.55
L 156 L (in) 6.14 M 27 M (in) 1.06 S 174	К	9
L (in) 6.14 M 27 M (in) 1.06 S 174	K (in)	0.35
M 27 M (in) 1.06 S 174	L	156
M (in) 1.06 S 174	L (in)	6.14
S 174	М	27
	M (in)	1.06
	S	174
S (in) 6.85	S (in)	6.85
T 48	Т	48
T (in) 1.89	T (in)	1.89

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

