
PHF TB2525X0.75



Bushing no. TB2525 d = Bore diameter (mm) 19 Bore diameter (in) 0.75 Keyway width (mm) 4.8 Keyway width (in) 0.19 Keyway depth (mm) 2.4 (mm) 85.7 A (in) 3.37 B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - F (in) - F (in) 1/2 X 1 Weight (kg) 2.045 Weight (lbs) 4.51		
(mm) 0.75 Keyway width (mm) 4.8 (mm) 0.19 Keyway width (in) 0.19 Keyway depth (mm) 2.4 (mm) 85.7 A (in) 3.37 B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - F (in) - F (in) 1/2 X 1 Weight (kg) 2.045	Bushing no.	TB2525
Bore diameter (in) 0.75 Keyway width (mm) 4.8 (mm) 0.19 Keyway depth (mm) 2.4 (mm) 85.7 A (in) 3.37 B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	d = Bore diameter	19
Keyway width (mm) 4.8 Keyway width (in) 0.19 Keyway depth (mm) 2.4 (mm) 0.09 A (mm) 85.7 A (in) 3.37 B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	(mm)	
(mm) 0.19 Keyway width (in) 0.19 Keyway depth (mm) 2.4 (mm) 0.09 A (mm) 85.7 A (in) 3.37 B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - F (in) - F (in) 1/2 X 1 Weight (kg) 2.045	Bore diameter (in)	0.75
(mm) Keyway width (in) 0.19 Keyway depth (mm) 2.4 (mm) 0.09 A (mm) 85.7 A (in) 3.37 B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - F (in) - F (in) 1/2 X 1 Weight (kg) 2.045	Keyway width	4.8
Keyway width (in) 0.19 Keyway depth (mm) 2.4 (mm) 0.09 A (mm) 85.7 A (in) 3.37 B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045		
(mm) 0.09 A (mm) 85.7 A (in) 3.37 B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045		0.19
Keyway depth (in) 0.09 A (mm) 85.7 A (in) 3.37 B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	Keyway depth	2.4
Keyway depth (in) 0.09 A (mm) 85.7 A (in) 3.37 B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	(mm)	
A (in) 3.37 B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	L	0.09
B (mm) 63.5 B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	A (mm)	85.7
B (in) 2.5 D (mm) 82.6 D (in) 3.25 E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	A (in)	3.37
D (mm) 82.6 D (in) 3.25 E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	B (mm)	63.5
D (in) 3.25 E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	B (in)	2.5
E (mm) - E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	D (mm)	82.6
E (in) - F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	D (in)	3.25
F (mm) - F (in) 1/2 X 1 Weight (kg) 2.045	E (mm)	-
F (in) 1/2 X 1 Weight (kg) 2.045	E (in)	-
Weight (kg) 2.045	F (mm)	-
Weight (RS)	F (in)	1/2 X 1
Weight (lbs) 4.51	Weight (kg)	2.045
	Weight (lbs)	4.51



[®] SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.