

## PHC 3939X10FT





	Pitch P (mm)	203.2
	Pitch P (in)	8
Provide and a second	Roller diameter d1	23
	max (mm)	
	Roller diameter d1	0.91
	max (in)	
	Width between	27
	inner plates b1 min	
	(mm)	1.06
	Width between	1.00
	inner plates b1 min (in)	
	Pin diameter d2	11.1
	max (mm)	
	Pin length L max	49
	(mm)	
	Pin length L max	1.93
	(in)	
	Pin length Lc max	53.5
	(mm)	
	Pin length Lc max	2.11
	(in)	28.58
	Inner plate height h2 max	28.38
and a state of the	Inner plate height	1.13
	h2 max (in)	1.15
	Plate thickness T	4
	max (mm)	
	Plate thickness T	0.16
	max (in)	
A	Ultimate tensile	115.6
	strength Q min kN	

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



Ultimate tensile	25987.91
strength Q min (lb)	
Average tensile	136.5
strength Qo (kN)	
Average tensile	5.37
strength Qo (lb)	
Weight (kg/m)	2.45
Weight (lbs/ft)	1.65
1	/

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

