
Bushings and Hubs FX keyless bushings

## PHF FX50-22X47



Bushing no.	FX50
d (mm)	22
d (in)	0.87
D (mm)	47
d <sub>w</sub> (mm)	-
L (mm)	-
L <sub>1</sub> (mm)	26
L <sub>2</sub> (mm)	29
L₃ (mm)	42
B (mm)	48
D <sub>1</sub> (mm)	53
d <sub>1</sub> (mm)	-
e (mm)	-
F <sub>t</sub> Transmissible	33.6
axial force (kN)	
M <sub>t</sub> Transmissible	370
torque (Nm)	
P <sub>w</sub> Shaft surface	145
pressure (N/mm <sup>2</sup> )	(E
$P_n$ Hub surface	65
pressure (N/mm <sup>2</sup> )	6
Clamp screws Qty	*
Clamp screws size	M6
Clamp screws nut	-
M <sub>s</sub> Screw	17
tightening torque	
(Nm)	

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



Weight (kg)	0.5	

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

