
Bushings and Hubs FX keyless bushings

PHF FX50-32X60



Bushing no.	FX50
d (mm)	32
d (in)	1.26
D (mm)	60
d _w (mm)	-
L (mm)	-
L ₁ (mm)	26
L ₂ (mm)	29
L₃ (mm)	42
B (mm)	48
D ₁ (mm)	66
d ₁ (mm)	-
e (mm)	-
F _t Transmissible	51
axial force (kN)	
M _t Transmissible	810
torque (Nm)	
P _w Shaft surface	145
pressure (N/mm ²)	20
P _n Hub surface	80
pressure (N/mm ²)	9
Clamp screws Qty	9 M6
Clamp screws size	MO
Clamp screws nut	-
M _s Screw	17
tightening torque	
(Nm)	

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



Weight (kg)	0.7		

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

