
Bushings and Hubs FX keyless bushings

PHF FX50-70X110



Bushing no.	FX50
d (mm)	70
d (in)	2.76
D (mm)	110
d _w (mm)	-
L (mm)	-
L ₁ (mm)	40
L ₂ (mm)	45
L ₃ (mm)	56
B (mm)	66
D ₁ (mm)	117
d ₁ (mm)	-
e (mm)	-
F _t Transmissible	116
axial force (kN)	
M _t Transmissible	4000
torque (Nm)	110
P_w Shaft surface	110
pressure (N/mm ²)	70
P _n Hub surface pressure (N/mm²)	10
Clamp screws Qty	7
Clamp screws size	M10
Clamp screws nut	-
M _s Screw	83
tightening torque	
(Nm)	

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



Weight (kg)	2.5
-------------	-----

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

