
Bushings and Hubs FX keyless bushings

PHF FX52-18X55



Bushing no.	FX52
d (mm)	18
d (in)	0.71
D (mm)	55
d _w (mm)	-
L (mm)	-
L ₁ (mm)	17
L ₂ (mm)	22
L ₃ (mm)	30
B (mm)	38
D ₁ (mm)	62
d ₁ (mm)	-
e (mm)	-
F _t Transmissible	18.1
axial force (kN)	
M _t Transmissible	150
torque (Nm)	
P _w Shaft surface	160
pressure (N/mm²)	55
P _n Hub surface	55
pressure (N/mm ²) Clamp screws Qty	3
	M8
Clamp screws size	1410
Clamp screws nut	-
M _s Screw	25

 ® SKF is a registered trademark of the SKF Group
 © SKF Group 2012
 The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



tightening torque (Nm)		
Weight (kg)	0.5	

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising the second secon out of the use of the information contained herein.

