
PHF FX80-24X35



Bushing no.	FX80
d (mm)	24
d (in)	0.94
D (mm)	35
d _w (mm)	-
L (mm)	-
L ₁ (mm)	6.5
L ₂ (mm)	-
L ₃ (mm)	-
B (mm)	18
D ₁ (mm)	45
d ₁ (mm)	-
e (mm)	-
F _t Transmissible	8.75
axial force (kN)	
M _t Transmissible	105
torque (Nm)	105
P _w Shaft surface	185
pressure (N/mm²)	127
P _n Hub surface pressure (N/mm²)	127
Clamp screws Qty	-
ļ	
Clamp screws size	VMC
Clamp screws nut	KM6
M _s Screw	220
tightening torque	

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



(Nm)	
Weight (kg)	0.09

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

