
Bushings and Hubs FX keyless bushings

## PHF FX80-30X40



Bushing no.	FX80
d (mm)	30
d (in)	1.18
D (mm)	40
d <sub>w</sub> (mm)	-
L (mm)	-
L <sub>1</sub> (mm)	7
L <sub>2</sub> (mm)	-
L₃ (mm)	-
B (mm)	19.5
D <sub>1</sub> (mm)	52
d <sub>1</sub> (mm)	-
e (mm)	-
F <sub>t</sub> Transmissible	10.6
axial force (kN)	
M <sub>t</sub> Transmissible	160
torque (Nm)	
P <sub>w</sub> Shaft surface	164
pressure (N/mm <sup>2</sup> )	100
P <sub>n</sub> Hub surface	123
pressure (N/mm <sup>2</sup> )	_
Clamp screws Qty	-
Clamp screws size	-
Clamp screws nut	KM7
M <sub>s</sub> Screw	340
tightening torque	

 ® SKF is a registered trademark of the SKF Group
 © SKF Group 2012
 The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



(Nm)		
Weight (kg)	0.07	

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising the second secon out of the use of the information contained herein.

