
Bushings and Hubs FX keyless bushings

PHF FX90-17X25



Bushing no. FX90 d (mm) 17 d (in) 0.67 D (mm) 25 d _w (mm) - L (mm) - L_1 (mm) 20 L ₂ (mm) - L ₃ (mm) - B (mm) 32 D ₁ (mm) - e (mm) - Ft Transmissible axial force (kN) 9 Mt Transmissible torque (Nm) 80 Pw Shaft surface pressure (N/mm²) 70 Pressure (N/mm²) 45 pressure (N/mm²) 45 pressure (N/mm²) Clamp screws size KM4 Clamp screws nut Clamp screws nut - Ms Screw 160 tightening torque (Nm) 0.07		
d (ini) 0.67 D (mm) 25 d _w (mm) - L (mm) - L ₁ (mm) - L ₂ (mm) - L ₃ (mm) - B (mm) 32 D ₁ (mm) 32 d ₁ (mm) - e (mm) - F _t Transmissible 9 axial force (kN) 80 Mt Transmissible 80 torque (Nm) - P _w Shaft surface 70 pressure (N/mm ²) 45 pressure (N/mm ²) - Clamp screws Qty - Clamp screws size KM4 Clamp screws nut - M _s Screw 160 tightening torque 160	Bushing no.	FX90
D (mm) 25 dw (mm) - L (mm) - L_1 (mm) 20 L_2 (mm) - L_3 (mm) - B (mm) 32 D_1 (mm) 32 d_1 (mm) - e (mm) - Ft Transmissible 9 axial force (kN) 80 Mt Transmissible 80 torque (Nm) 70 Pw Shaft surface 70 pressure (N/mm²) 45 pressure (N/mm²) 45 Clamp screws Qty - Clamp screws nut - Ms Screw 160 tightening torque 160	d (mm)	17
dw (mm) - L (mm) - L_1 (mm) 20 L_2 (mm) - L_3 (mm) - B (mm) 32 D_1 (mm) 32 d_1 (mm) - e (mm) - Ft Transmissible 9 axial force (kN) 80 Mt Transmissible 80 torque (Nm) 70 Pw Shaft surface 70 pressure (N/mm²) 45 pressure (N/mm²) 45 Clamp screws Qty - Clamp screws nut - Ms Screw 160 tightening torque 160	d (in)	0.67
L (mm) - L_1 (mm) 20 L_2 (mm) - L_3 (mm) - B (mm) 32 D_1 (mm) 32 d_1 (mm) - e (mm) - F_t Transmissible 9 axial force (kN) 80 Mt Transmissible 70 pressure (N/mm²) 70 P_n Hub surface 45 pressure (N/mm²) - Clamp screws Qty - Clamp screws nut - Ms Screw 160 tightening torque 160	D (mm)	25
L_1 (mm) 20 L_2 (mm) - L_3 (mm) 32 D_1 (mm) 32 D_1 (mm) - e (mm) - e (mm) - Ft Transmissible 9 axial force (kN) 80 Mt Transmissible 80 torque (Nm) 70 Pw Shaft surface 70 pressure (N/mm²) 45 pressure (N/mm²) - Clamp screws Qty - Clamp screws nut - Ms Screw 160 tightening torque 160	d _w (mm)	-
L1L2L2L2(mm)-L3 (mm)32D1 (mm)32D1 (mm)-e (mm)-e (mm)-Ft Transmissible9axial force (kN)80Mt Transmissible80torque (Nm)70Pw Shaft surface70pressure (N/mm²)45pressure (N/mm²)45Clamp screws Qty-Clamp screws nut-Ms Screw160tightening torque160	L (mm)	-
L3 (mm)-B (mm)32D1 (mm)32d1 (mm)-e (mm)-e (mm)-Ft Transmissible9axial force (kN)80Mt Transmissible80torque (Nm)70Pw Shaft surface70pressure (N/mm²)45Pressure (N/mm²)-Clamp screws Qty-Clamp screws nut-Ms Screw160tightening torque160	L ₁ (mm)	20
B (mm)32D1 (mm)32d1 (mm)-e (mm)-F (mm)-F Transmissible9axial force (kN)80Mt Transmissible torque (Nm)80Pw Shaft surface pressure (N/mm²)70Pn Hub surface pressure (N/mm²)45Pressure (N/mm²)-Clamp screws Qty tightening torque (Nm)-	L ₂ (mm)	-
D1 (mm)32D1 (mm)32d1 (mm)-e (mm)-Ft Transmissible9axial force (kN)80Mt Transmissible80torque (Nm)70Pw Shaft surface70pressure (N/mm²)45Pn Hub surface45pressure (N/mm²)-Clamp screws Qty-Clamp screws nut-Ms Screw160tightening torque160	L₃ (mm)	-
D1 (mm)Image: Second secon	B (mm)	32
e (mm) - F _t Transmissible 9 axial force (kN) 80 torque (Nm) 70 P _w Shaft surface 70 pressure (N/mm ²) 45 pressure (N/mm ²) Clamp screws Qty - Clamp screws nut - M _s Screw 160 tightening torque (Nm)	D ₁ (mm)	32
Ft Transmissible axial force (kN)9Mt Transmissible torque (Nm)80Pw Shaft surface pressure (N/mm²)70Pn Hub surface pressure (N/mm²)45Clamp screws Qty-Clamp screws sizeKM4Clamp screws nut tightening torque (Nm)-	d ₁ (mm)	-
axial force (kN) 80 Mt Transmissible 80 torque (Nm) 70 Pw Shaft surface 70 pressure (N/mm²) 45 Pressure (N/mm²) - Clamp screws Qty - Clamp screws nut - Ms Screw 160 tightening torque (Nm)	e (mm)	-
Mt Transmissible torque (Nm)80Pw Shaft surface pressure (N/mm²)70Pn Hub surface pressure (N/mm²)45Clamp screws Qty-Clamp screws size torque screws nutKM4Clamp screws nut tightening torque (Nm)-	F _t Transmissible	9
International conductionStatetorque (Nm)70Pw Shaft surface70pressure (N/mm²)45pressure (N/mm²)70Clamp screws Qty-Clamp screws sizeKM4Clamp screws nut-Ms Screw160tightening torque(Nm)	axial force (kN)	
Pw Shaft surface pressure (N/mm²)70Pn Hub surface pressure (N/mm²)45Clamp screws Qty-Clamp screws sizeKM4Clamp screws nut-Ms Screw tightening torque (Nm)160	M _t Transmissible	80
pressure (N/mm²)45Pn Hub surface pressure (N/mm²)45Clamp screws Qty-Clamp screws sizeKM4Clamp screws nut-Ms Screw tightening torque (Nm)160	torque (Nm)	
Pn Hub surface pressure (N/mm²)45Clamp screws Qty-Clamp screws sizeKM4Clamp screws nut-Ms Screw tightening torque (Nm)160		70
pressure (N/mm²) Clamp screws Qty Clamp screws size KM4 Clamp screws nut - Ms Screw tightening torque (Nm)		
Clamp screws Qty-Clamp screws sizeKM4Clamp screws nut-Ms Screw160tightening torque(Nm)		45
Clamp screws sizeKM4Clamp screws nut-Ms Screw160tightening torque(Nm)		
Clamp screws nut - M _s Screw 160 tightening torque (Nm)	Clamp screws Qty	-
M _s Screw 160 tightening torque (Nm)	Clamp screws size	KM4
tightening torque (Nm)	Clamp screws nut	-
(Nm)	M _s Screw	160
Weight (kg) 0.07	(Nm)	
	Weight (kg)	0.07

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

