
Bushings and Hubs FX keyless bushings

## PHF FX120-38X60



Bushing no.	FX120
d (mm)	38
d (in)	1.5
D (mm)	60
d <sub>w</sub> (mm)	-
L (mm)	-
L <sub>1</sub> (mm)	15
L <sub>2</sub> (mm)	22
L₃ (mm)	-
B (mm)	28
D <sub>1</sub> (mm)	-
d <sub>1</sub> (mm)	-
e (mm)	-
F <sub>t</sub> Transmissible	-
axial force (kN)	
M <sub>t</sub> Transmissible	680
torque (Nm)	
P <sub>w</sub> Shaft surface	170
pressure (N/mm²)	
P <sub>n</sub> Hub surface	100
pressure (N/mm²)	
Clamp screws Qty	12
Clamp screws size	M6
Clamp screws nut	-

 ® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



M <sub>s</sub> Screw	16
tightening torque	
(Nm)	
Weight (kg)	-

 SKF is a registered trademark of the SKF Group
SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising the second s out of the use of the information contained herein.

