
Bushings and Hubs FX keyless bushings

## PHF FX190-280X460



	Bushing no.	FX190
	d (mm)	280
A	d (in)	11.02
	D (mm)	460
	d <sub>w</sub> (mm)	210
	L (mm)	134
And and a second	L <sub>1</sub> (mm)	114
A	L <sub>2</sub> (mm)	-
	L₃ (mm)	-
	B (mm)	0
Provide states	D <sub>1</sub> (mm)	-
	d <sub>1</sub> (mm)	346
deserves of	e (mm)	10
	F <sub>t</sub> Transmissible	2090
	axial force (kN)	
Contraction of the local distance of the loc	M <sub>t</sub> Transmissible	217000
	torque (Nm)	
	P <sub>w</sub> Shaft surface	-
111111	pressure (N/mm²)	
	P <sub>n</sub> Hub surface	-
	pressure (N/mm²)	
	Clamp screws Qty	16
	Clamp screws size	M20
	Clamp screws nut	-
Lange and the second se	M <sub>s</sub> Screw	490
	tightening torque	
and a state of the	(Nm)	
	Weight (kg)	102

® SKF is a registered trademark of the SKF Group
© SKF Group 2012

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

