
PHE 110GCRRSB



Size	110 GCR
Power per 100	4320
r/min (kW)	
Power per 100	5790.88
r/min (HP)	
Rated torque (Nm)	413000
Rated torque (lbft)	304613.17
Speed Max. (r/min)	1330
Bore diameter Min.	140
(mm)	
Bore diameter Min.	5.51
(in)	
Bore diameter	445
Max. (mm)	
Bore diameter	17.52
Max. (in)	
A (mm)	775
A (in)	30.51
B (mm)	686
B (in)	27.01
E (mm)	9.7
E (in)	0.38
F (mm)	749
F (in)	29.49
H (mm)	50.8
H (in)	2
L (mm)	333
L (in)	13.11
Q (mm)	322

 ® SKF is a registered trademark of the SKF Group
 © SKF Group 2012
 The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



Q (in)	12.68
Gap G (mm)	19
Gap G (in)	0.75
Coupling mass	1610
without bore (kg)	1010
Coupling mass without bore (lbs)	3549.44

® SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising the second secon out of the use of the information contained herein.

