
PHE 35GCSET



Size	35 GC
Power per 100	194
r/min (kW)	
Power per 100	260.05
r/min (HP)	
Rated torque (Nm)	18500
Rated torque (lbft)	13644.9
Speed Max. (r/min)	3900
Bore diameter Min. (mm)	51
Bore diameter Min.	2.01
(in)	
Bore diameter	134
Max. (mm)	
Bore diameter	5.28
Max. (in)	
A (mm)	279
A (in)	10.98
B (mm)	218
B (in)	8.58
C (mm)	106
C (in)	4.17
D (mm)	178
D (in)	7.01
F (mm)	211
F (in)	8.31
H (mm)	28.4
H (in)	1.12
J (mm)	98
J (in)	3.86



[®] SKF is a registered trademark of the SKF Group
© SKF Group 2012
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

M (mm)	130
M (in)	5.12
Gap G Min. (mm)	6
Gap G Min. (in)	0.24
Lubricant mass (kg)	0.54
Lubricant mass (lbs)	1.19
Coupling mass	68
without bore and	
min. DBSE (kg)	
Coupling mass	149.91
without bore and	
min. DBSE (lbs)	
Weight (kg)	68
Weight (lbs)	149.91

